



IR Thermometer with Color Alert

High/Low Alarms with Vision Alarm Function If the user-settable alarm setpoints are exceeded, the screen will flash red

Features:

- Fast and accurate measurements at 12" where the two lasers converge with 12:1 field of view
- Measures up to 950°F (510°C)
- Automatic blue backlit dual LCD display
- Red backlit display flashes when reading exceeds High or Low set points
- Exclusive 150 millisecond instantaneous response for capturing spikes in temperature
- Max mode captures and holds rapidly changing temperatures
- Lock function for continuous readings (disables auto power off)
- Adjustable emissivity increases measurement accuracy for different surfaces
- Adjustable High/Low set points with audible alarm alerts user when temperature exceeds the programmed set points
- Double molded housing
- Complete with case and 9V battery



Dual Color Display — Easy visual alert when temperature exceeds user programmed MAX and MIN setpoints, the display flashes from Blue to Red. Red backlit display will continue to flash until normal temperature is reached.

Ordering Information:

4250912" distance Dual Laser InfraRed Thermometer 42509-NIST....12" dist. Dual Laser InfraRed Thermometer w/ NIST



Specifications Laser Convergence Distance 12" (30.5cm) Range -4 to 950°F (-20 to 510°C) Repeatability ±0.5% or 1.8°F/1°C **Basic Accuracy** ±(1% of rdg + 2°F/1°C) Max resolution 0.1°F/°C 0.10 to 1.00 Adjustable Emissivity Field of View (Distance to Target) 12:1 5.7x4x1.6" (146x104x43mm) Dimensions Weight 5.7oz (163g)

