

HOBO Pendant Temperature/Light Data Logger 64K - UA-002-64



Measures:

Temperature, Light Intensity, Water Temp

| | | | |
|------|------|-------|------|
| Qty | 1-9 | 10-99 | 100+ |
| \$US | \$64 | \$60 | \$54 |

Contact Onset at 1-800-564-4377


Description:



Optical Interface for data transfer - [click to zoom](#) This miniature [data logger](#) can record [temperature](#) and relative light levels. Complete with [waterproof](#) casing, this product is designed for indoor, outdoor, and underwater deployment. This model can store approximately 52,000 measurements of 10-bit readings.

- Low-cost temperature with alarm indication or light intensity
- Waterproof housing for wet or underwater use
- Data readout in less than 30 seconds via fast Optic USB interface


Detailed Specifications:



Plot A

Measurement range

Temperature: -20° to 70° (-4° to 158°)
 Light: 0 to 320,000 lux (0 to 30,000 lumens/ft²)



Plot B

Accuracy:

Temperature: $\pm 0.53^\circ\text{C}$ from 0° to 50°C ($\pm 0.95^\circ\text{F}$ from 32° to 122°F), see Plot A

Light intensity: Designed for measurement of relative light levels, see Plot D for light wavelength response

Resolution:

Temperature: 0.14°C at 25°C (0.25°F at 77°F), see Plot A

Drift: Less than $0.1^\circ\text{C}/\text{year}$ ($0.2^\circ\text{F}/\text{year}$)

Response time:

Airflow of 2 m/s (4.4 mph): 10 minutes, typical to 90%


Water: 5 minutes, typical to 90%

Time accuracy: ± 1 minute per month at 25°C (77°F), see Plot B

Operating range

In water/ice: -20° to 50°C (-4° to 122°F)

In air: -20° to 70°C (-4° to 158°F)



Plot C

Water depth rating: 30 m from -20° to 20°C (100 ft from -4° to 68°F),

see Plot C


NIST traceable certification: Available for temperature only at additional charge; temperature range -20° to 70°C (-4° to 158°F)

Battery life: 1 year typical use

Memory

UA-002-08: 8K bytes (approximately 3.5K combined temperature and light readings or events)

UA-002-64: 64K bytes (approximately 28K combined temperature and light readings or events)



Plot D

Materials: Polypropylene case; stainless steel screws; Buna-N o-ring

Weight: 18 g (0.6 oz)

Dimensions: 58 x 33 x 23 mm (2.3 x 1.3 x 0.9 inches)

The CE Marking identifies this product as complying with the relevant directives in the European Union (EU).

HOB0 Data Loggers

1-800-LOGGERS