

TidbiT v2 Water Temperature Data Logger - UTBI-001

Max Depth 1,000 ft



Measures:

Temperature, Water Temp

Qty	1-9	10-99	100+
\$US	\$133	\$124	\$113

Contact Onset at 1-800-564-4377

Description:

Only 3x4 cm, this tiny [data logger](#) measures temperatures over a wide [temperature](#) range. The TidbiT v2 provides 12-bit resolution and has ± 0.2 °C accuracy. It is designed for outdoor and underwater environments and is [waterproof](#) to 300 m (1000 ft). An optical [USB](#) interface allows users to offload data in seconds. Please note, a solar radiation shield is required to obtain accurate air temperature measurements in sunlight (RS1 Solar Radiation Shield, assembly required; or M-RSA pre-assembled Solar Radiation Shield).



Optical interface for data transfer - [click to zoom](#)

Features:

- Onset's smallest temperature data logger
- Waterproof to 300 meters (1,000 feet)
- Data readout in less than 30 seconds via fast Optic USB interface

Detailed Specifications:

Temperature Sensor

Operation range: *
 -20Â° to 70Â°C (-4Â° to 158Â°F) in air;
 maximum sustained temperature of 30Â°C (86Â°F) in water*

Accuracy: 0.2Â°C over 0Â° to 50Â°C (0.36Â°F over 32Â° to 122Â°F)

Resolution: 0.02Â°C at 25Â°C (0.04Â°F at 77Â°F)

Response time: 5 minutes in water; 12 minutes in air moving 2 m/sec; 20 minutes in air moving 1 m/sec (typical to 90%)

Stability (drift): 0.1Â°C (0.18Â°F) per year

Logger

Real-time clock: ± 1 minute per month 0Â° to 50Â°C (32Â° to 122Â°F)

Battery: 3 Volt lithium, non-replaceable

Battery life (typical use): 5 years with 1 minute or greater logging interval

Memory (non-volatile): 64K bytes memory (approx. 42,000 12-bit temperature measurements)

Weight: 19.6 g (0.69 oz)

Dimensions: 3.0 Ã— 4.1 Ã— 1.7 cm (1.2 Ã— 1.6 Ã— 0.68 in.); mounting bail 4.6 mm (3/16 in.) diameter hole

Wetted materials: Epoxy case

Waterproof: To 305 m (1000 ft.)

Logging interval: Fixed-rate or multiple logging intervals, with up to 8 user-defined logging intervals and durations; logging intervals from 1 second to 18 hours. Refer to HOBOWare software manual.

Launch modes: Immediate start, delayed start

Offload modes: Offload while logging; stop and offload

Battery indication: Battery level can be viewed in status screen and optionally logged in datafile. Low battery indication in datafile.

NIST certificate: Available for additional charge

The CE Marking identifies this product as complying with the relevant directives in the European Union (EU).

* To guarantee accuracy, the TidbiT v2 Temp must not be used in condensing environments and water temperatures higher than 30C (86F) for more than eight cumulative weeks over the life of the logger. Frequent or prolonged exposure will lead to measurement drift and eventual failure.

HOB0[®] Data Loggers

1-800-LOGGERS