## HOBO U12 Deep Ocean Temperature Logger - U12-015-03

#### Measures:

Temperature, Water Temp



- Features:
  - 11,000m depth rating (36,080 ft)
  - Extended temperature range:- -40 to 125C
  - Titanium housing for use in saltwater
  - Fast readout via direct USB interface
  - Compatible with HOBOware and HOBOware Pro
  - software for logger setup, graphing and analysis

#### Qty \$US 10-99 100+ 1-9 \$799 \$743 \$679


Contact Onset at 1-800-564-4377

#### **Description:**

The HOBO U12 Deep Ocean Water Temperature Logger is a single-channel water <u>temperature</u> logger with 12-bit resolution that can record up to 43,000 measurements. With its robust titanium housing, this logger is designed to withstand ocean extremes of depth and temperature.

### **Detailed Specifications:**

Measurement Range:	-40° to 125°C (-40° to 257°F)
Accuracy:	±0.22°C at 25°C (±0.4°F at 77°F), see Plot A below
Resolution:	0.025°C at 25°C (0.045°F at 77°F), see Plot A below
Drift:	0.05°C/year + 0.1°C/1000 hrs above 100°C (0.09°F + 0.2°F/1000 hrs above 212°F
Response Time in Water:	< 4 minutes, typical to 90%
Time Accuracy:	±2 minute per month at 25°C (77°F), see Plot B below
Operating Environment:	Air, water, steam, 0 to 100% RH
Operating Temperature:	Logging: -40º to 125ºC (-40º to 257ºF) Launch/Readout: 0º to 50ºC (32º to 122ºF), per USB specification
Battery Life:	3 years typical use, factory replaceable
Memory	64K bytes (43,000 12-bit measurements)
Construction	Titanium with O-ring seals and backup rings
Weight	105 g (3.7 oz)
Size:	114 x 20.6 mm diameter (4.5 x 0.81 in. diameter)
Depth Rating:	11,000 m (36,080 ft)
Pressure Rating:	1110 bar (16,000 psi)
Vibration Rating:	Navy spec: NAVMAT P-9492
NIST Certificate:	Available for additional charge; temperature range -30Ű to 120ŰC (-22Ű to 248ŰF)
CE	The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).





Plot B



# 1-800-LOGGERS