


HOBO[®] U12 Stainless Temp Logger

High-accuracy temperature monitoring for challenging process conditions

HOBO U12 Stainless Temperature data loggers are ideal for food, pharmaceutical, autoclave, and other applications where high-accuracy temperature data is critical. They can withstand process conditions from pasteurization to flash freezing and washdown.



HOBO U12 Stainless Temperature Logger

Supported Measurements: Temperature



HOBO U12 Stainless Temperature Logger with 5-inch Probe

Key Advantages:

- High-accuracy, extended temperature range
- Suitable for high pressure applications to 2200 psi
- Fast readout via direct USB interface

Minimum System Requirements:



Software



USB cable*

*USB cable included with software

► For complete information and accessories, please visit: www.onsetcomp.com

Part number	U12-015	U12-015-02
Memory	43,000 measurements	
Battery life	3 year typical, factory replaceable	
Response time	10 minutes (to 90% in airflow of 1 m/s) 3.5 minutes (to 90% in water)	2.25 minutes (to 90% in airflow of 1 m/s) 20 seconds (to 90% in water)
Operating range	Logging: -40° to 125°C (-40° to 257°F) Launch/readout: 0° to 50°C (32° to 122°F), per USB specification	
Range	-40° to 125°C (-40° to 257°F)	
Accuracy	± 0.25°C from 0° to 50°C (± 0.45°F from 32° to 122°F)	Accuracy: ± 0.25°C from 0° to 50°C (± 0.45°F from 32° to 122°F)
Resolution	0.03°C at 25°C (0.05°F at 77°F)	0.03°C at 25°C (0.05°F at 77°F)
Dimensions	17.5 x 101.6 mm (0.69 x 4.00 in)	Logger: 17.5 x 101.6 mm (0.69 x 4.00 in) Probe: 4 x 124 mm (0.16 x 4.90 in)
CE compliant	Yes	

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-800-564-4377
- Fax 508-759-9100

Technical Support

- (8am to 8pm ET, Monday through Friday)
- Contact [Product Support](#)
- Call 877-564-4377