

HOBO U14 LCD Data Logger - External Temperature/RH - U14-002



Measures:

Temperature, Relative Humidity

Features:

- Faster USB data download time
- Improved Temp/RH sensor resolution
- Real-time display of Temperature and RH
- Alarm display and output ensure timely notification of out-of-range conditions
- Two models to choose from - [internal Temp/RH](#) or external Temp or Temp/RH
- Optional [Remote Alarm](#) and [Autodialer](#)
- Optional protective case for wet or condensing environments
- Compatible with HOBOWare and HOBOWare Pro software for logger setup, graphing and analysis

Qty	1-9	10-99	100+
\$US	\$186	\$173	\$158

Contact Onset at 1-800-564-4377

Description:

The HOBO U14 LCD External Temperature/[Relative Humidity \(RH\)](#) Data Logger displays and records [temperature](#) and humidity conditions. It is well-suited for use in manufacturing, processing, and storage environments where reliable monitoring and documentation of specific temp/RH conditions are critical. Data is offloaded via [USB](#) to a PC or Mac computer. An alarm display and built-in relay for use with [Onset's Remote Alarm](#) and/or [Autodialer](#) accessories assure timely notification of alarm conditions.

NOTE: The U14-002 requires the use of external temperature and relative humidity sensors. Sensor options can be found under the Compatible Items tab below.

Detailed Specifications:

Environmental

- Operating temperature range -20Â°C to +50Â°C, (-4Â°F to +122Â°F) , 0 to 100% RH non-condensing
- Operating relative humidity range 0 to 95%, non-condensing, noncorrosive environment

Logger Capabilities

- Capacity:
 - Temp and RH: 21,500 measurements
 - Temp Only: 43,000 measurements
- Software-selectable sampling intervals: 1 second up to 18 hours, recording times up to 1 year
- Programmable start time/date
- Recording modes: Stop when full
- Launch Modes: Immediate, Delayed
- Nonvolatile EEPROM memory retains data even if batteries fail

LCD

- Size: 33 x 50.8 mm (1.3 x 2 inches)
- Displays temperature and relative humidity simultaneously
- Displays Â°C or Â°F (selectable within host software)
- Displays memory remaining and battery level
- Displays flashing ALERT for out-of-limits conditions (selectable within host software) and stops flashing on offload or return to normal range.

Alarms

- High and low set points for both temperature and relative humidity
- Selectable delays for each set point.
- Alert conditions reset on offload or return to normal range.
- Selectable Contact Relay: Normally Closed or Normally Open
- Contact rating: 48VDC, 1A max
- Contact resistance: less than 1 Ohm
- Wire size range is 22AWG to 14AWG
- 0% Low Battery Range Communications
- Offloads data to PC or U-Shuttle via USB cable

- Readout full logger (64K) in less than 30 seconds

Timekeeping

- Time accuracy: ± 1 minute per month at $+20^{\circ}\text{C}$ ($+68^{\circ}\text{F}$).

Power

- 3 AAA Alkaline batteries, user-replaceable

Size/Weight

- 125 x 92 x 31 mm (4.9 x 3.6 x 1.2 inches)
- 170 g (6.0 oz) with batteries

External Sensors

For External Sensor Specifications, see the sensor's user manual.

Battery Life

The batteries will last one year in typical conditions (logging intervals of ≈ 1 minute with weekly offloads and average temperatures greater than 10°C or $+50^{\circ}\text{F}$). Frequent offloads and/or extreme temperatures will reduce battery life.

At temperatures below freezing (0°C or $+32^{\circ}\text{F}$), batteries will typically require replacement every six months. In these conditions the battery level bar graph should be checked regularly.

HOB0[®] Data Loggers**1-800-LOGGERS**