

## HOBO U20 Water Level Data Logger - U20-001-02

### 100-Foot Depth - freshwater



#### Measures:

Temperature, Barometric Pressure, Water Level

#### Features:

- Lightning protection - no long signal wires, and electronics are shielded in stainless steel housing for use in freshwater (see the [Water Level logger sensor location drawing](#))
- HOBOWare Pro software provides easy conversion to accurate water level reading, fully compensated for barometric pressure ([see demo](#)) temperature, and water density.
- Multiple-rate sampling ([see demo](#)) allows faster sampling at critical times such as when pumping starts or stops.
- Available in 4 depth ranges
- Ideal for use in wells, streams, lakes, wetlands and tidal areas
- No-vent-tube design for easy reliable deployment
- Available in stainless and titanium versions
- Durable ceramic pressure sensor
- 3-point NIST-traceable calibration certificate included

Qty	1-9	10-99	100+
\$US	\$495	\$460	\$421

Contact Onset at 1-800-564-4377

#### Description:

The HOBO Water Level [data logger](#) features high accuracy at a great price and ease-of-use, with no cumbersome vent tubes or desiccants to maintain. This [data logger](#) is ideal for recording [water levels](#) and [temperatures](#) in shallow wells, streams, lakes and freshwater wetlands.

View how the [HOBO Water Level Logger compares to the Competition](#).

#### Detailed Specifications:

##### Pressure and Water Level Measurements U20-001-02 and U20-001-02-Ti

<b>Operation Range</b>	0 to 400 kPa (0 to 58 psia); approximately 0 to 30.6 m (0 to 100 ft) of water depth at sea level, or 0 to 33.6 m (0 to 111 ft) of water at 3,000 m (10,000 ft) of altitude
<b>Factory Calibrated Range</b>	69 to 400 kPa (10 to 58 psia), 0Â° to 40Â°C (32Â° to 104Â°F)
<b>Burst Pressure</b>	500 kPa (72.5 psia) or 40.8 m (134 ft) depth
<b>Water Level Accuracy*</b>	Typical error: Â±0.05% FS, 1.5 cm (0.05 ft) water Maximum error: Â±0.1% FS, 3 cm (0.1 ft) water
<b>Raw Pressure Accuracy**</b>	Â±0.3% FS, 1.20 kPa (0.17 psi) maximum error
<b>Resolution</b>	<0.04 kPa (0.006 psi), 0.41 cm (0.013 ft) water
<b>Pressure Response Time (90%)***</b>	<1 second; measurement accuracy also depends on temperature response time
<b>Temperature Measurements (All Models)</b>	
<b>Operation Range</b>	-20Â° to 50Â°C (-4Â° to 122Â°F)
<b>Accuracy</b>	Â±0.44Â°C from 0Â° to 50Â°C (Â±0.79Â°F from 32Â° to 122Â°F), see Plot A
<b>Resolution</b>	0.10Â°C at 25Â°C (0.18Â°F at 77Â°F), see Plot A
<b>Response Time (90%)</b>	5 minutes in water (typical)

<b>Stability (Drift)</b>	0.1°C (0.18°F) per year
<b>Logger</b>	
<b>Real-time Clock</b>	± 1 minute per month 0°C to 50°C (32°F to 122°F)
<b>Battery</b>	2/3 AA, 3.6 Volt lithium, factory-replaceable
<b>Battery Life (Typical Use)</b>	5 years with 1 minute or greater logging interval
<b>Memory (Non-volatile)</b>	64K bytes memory (approx. 21,700 pressure and temperature samples)
<b>Weight</b>	Stainless steel models: approximately 210 g (7.4 oz) Titanium models: approximately 140 g (4.8 oz)
<b>Dimensions</b>	2.46 cm (0.97 inches) diameter, 15 cm (5.9 inches) length; mounting hole 6.3 mm (0.25 inches) diameter
<b>Wetted Materials</b>	316 stainless steel, Viton® o-rings, acetyl cap, ceramic sensor
<b>Logging Interval</b>	Fixed-rate or multiple logging intervals, with up to 8 user-defined logging intervals and durations; logging intervals from 1 second to 18 hours. Refer to the HOBOWare software manual.
<b>Launch Modes</b>	Immediate start and delayed start
<b>Offload Modes</b>	Offload while logging; stop and offload
<b>Battery Indication</b>	Battery voltage can be viewed in status screen and optionally logged in datafile. Low battery indication in datafile.



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

\* Water Level Accuracy: With accurate reference water level measurement, known water density, accurate Barometric Compensation Assistant data, and a stable temperature environment.

\*\* Raw Pressure Accuracy: Absolute pressure sensor accuracy includes all sensor drift, temperature, and hysteresis-induced errors.

\*\*\* Changes in Temperature: Allow 10 minutes in water to achieve full temperature compensation of the pressure sensor. Maximum error due to rapid thermal changes is approximately 0.5%.

