

HOBO[®] Dissolved Oxygen Logger

Affordable, high performance dissolved oxygen monitoring

The HOBO U26 Dissolved Oxygen Logger measures concentrations of dissolved oxygen in lakes, streams, rivers, estuaries, and coastal waters. Used by aquatic biologists, hydrologists, and other research professionals to monitor water quality, the U26 is ideal for climate change and environmental impact studies as well as ecological and oceanographic research.



The HOBO U26 combines the high-accuracy, robust performance of industry-leading RDO[®] Basic (Rugged Dissolved Oxygen) sensor technology with an easy-to-maintain design, all at a fraction of the cost of other monitoring options.

Supported Measurements: Dissolved Oxygen, Temperature

Key Advantages:

- Affordable, high performance DO monitoring with 0.2 mg/L accuracy
- Optical DO sensor technology for long-lasting calibration, less maintenance
- Software corrects for measurement drift from fouling; provides salinity-adjusted DO concentration and percent saturation (Salinity adjustment requires salinity meter reading or data logger file. Percent saturation requires barometric pressure data file.)
- Optic USB interface for high-speed, reliable data offload
- Easy-to-replace DO sensor cap lasts six months

Minimum System Requirements:



Software



Base Station*



Coupler¹

*HOBO Base Station or HOBO Waterproof Shuttle required.

¹Coupler included with HOBO Base Station or HOBO Waterproof Shuttle.

► For complete information and accessories, please visit: www.onsetcomp.com

Part number	U26-001
Dissolved Oxygen	
Sensor Type	Optical
Measurement Range	0 to 30 mg/L
Calibrated Range	0 to 20 mg/L; 0 to 35°C (32 to 95°F)
Accuracy	0.2 mg/L up to 8 mg/L; 0.5 mg/L from 8 to 20 mg/L
Resolution	0.02 mg/L
Response time	To 90% in less than 2 minutes
DO Sensor Cap Life	6 months (cap expires 7 months after initialization)
Temperature	
Operating Temperature and Measurement Range	-5 to 40°C (23 to 104°F), non-freezing
Temperature Accuracy	0.2°C (0.36°F)
Temperature Resolution	± 0.02°C (± 0.04°F)
Response Time	To 90% in less than 30 minutes
Logger	
Memory	21,700 sets of DO and temperature measurements
Logging Rate	1 minute to 18 hours
Time Accuracy	± 1 minute per month at 25°C (77°F)
Battery	3.6 V lithium battery; factory replaceable, life: 3 years (at 1 minute logging)
Maximum Depth	100 m (328 ft)
Dimensions	39.6 mm diameter x 266.7 mm (1.56 in diameter x 10.5 in)
CE Compliant	Yes

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- Email sales@onsetcomp.com
- Call 1-800-564-4377
- Fax 508-759-9100

Technical Support

- (8am to 8pm ET, Monday through Friday)
- Contact [Product Support](#)
- Call 877-564-4377