

HOBO UX100 Temperature Data Logger - UX100-001



Measures:

Temperature

Features:

- Easy-to view LCD display
- Large memory capacity
- Visual high & low alarm thresholds
- New Burst and Statistics logging modes
- Compatible with HOBOWare and HOBOWare Pro software for logger setup, graphing and analysis

Qty	1-9	10-99	100+
\$US	\$75	\$70	\$64

Contact Onset at 1-800-564-4377

Description:

The HOBO UX100-001 Temp [data logger](#) records temperature in indoor environments with its integrated sensor. The logger is ideal for monitoring occupant comfort in office buildings, tracking food storage conditions in warehouses, and logging [temperature](#) trends in server rooms.

Detailed Specifications:

Temperature Sensor

Range: -20Â° to 70Â°C (-4Â° to 158Â°F)

Accuracy: $\pm 0.21\text{Â}^\circ\text{C}$ from 0Â° to 50Â°C ($\pm 0.38\text{Â}^\circ\text{F}$ from 32Â° to 122Â°F), see Plot A

Resolution: 0.024Â°C at 25Â°C (0.04Â°F at 77Â°F); see Plot A

Response Time: 8 minutes in air moving 1 m/s (2.2 mph)

Drift: <0.1Â°C (0.18Â°F) per year

Logger

Logger Operating Range:

Logging: -20Â° to 70Â°C (-4Â° to 158Â°F); 0 to 95% RH (non-condensing)
 Launch/Readout: 0Â° to 50Â°C (32Â° to 122Â°F) per USB specification

Logging Rate: 1 second to 18 hours, 12 minutes, 15 seconds

Logging Modes: Normal, Burst or Statistics

Memory Modes: Wrap when Full or Stop when Full

Start Modes: Immediately, Push Button, Date & Time or Next Interval

Stop Modes: When Memory Full, Push Button, or Date & Time

Restart Mode: Push Button

Time Accuracy: ± 1 minute per month at 25Â°C (77Â°F), see Plot B


Battery Life: 1 year, typical with logging rate of 1 minute and sampling interval of 15 seconds or greater

Memory: 128 KB (84,650 measurements, maximum)


Download Type: USB 2.0 interface

Full Memory Download Time: 20 seconds

LCD: LCD is visible from: 0° to 50°C (32° to 122°F); the LCD may react slowly or go blank in temperatures outside this range



Plot A: Temperature Accuracy and Resolution




Size

: 3.66 x 5.94 x 1.52 cm (1.44 x 2.34 x 0.6 in.)

Weight: 23 g (0.81 oz)

Environmental Rating: IP50

CE - The CE Marking identifies this product as complying with all relevant directives in the European Union (EU)



Plot B: Time Accuracy

HOB0 Data Loggers

1-800-LOGGERS